



## ScriptTag Classic

### Key features

- **Read/write capability**
- **"Credit card" - size**
- **Licence-free worldwide**

The ScriptTag Classic is the ideal choice of ID-tag in parking and access control applications that ask for hands-free access and where there is a demand for storing information on the ID-tag. The ScriptTag can store up to 606 bits of data. The ScriptTag Classic is a read/write 2.45 GHz RFID tag. Each ID-tag has a pre-programmed 8-digit unique identity code and a 32 bit checksum to ensure a very safe read. In combination with a random reflection of the reader signal, this eliminates substitution errors even with several ID-tags identified simultaneously. A separate data field in the ID-tag is used for storing data of up to 606 bits (82 ASCII 7 bit + check). This data field can be reprogrammed many times.

The ID-tag is battery powered, keeping the ID-tag alert, for instantaneous reflection of the reader signal. The lifetime of the ScriptTag Classic is therefore +6 years, depending on configuration and temperature.

Data	
Operating frequencies	2.435 GHz to 2.465 GHz
Read range*	Example: Up to 6 metres with LR-6 reader
Read cycle	Random mode
Dimensions	86x54x3 mm (3.39x1.61x0.12 in)
Material	Polymers
Battery lifetime	Typically +6 years. Lifetime is dependent on temperature.
Operating temperatures	-20 °C (-4 °F) to +85 °C (+185 °F)
Encapsulation	IP54
Colour	Grey scale
Certifications	CE Certificate according to R&TTE-Directive 1999/5/EC, Annex IV, Health: 1999/519/EC, El.Safety: EN 60950, EMC: EN 301489-3:2000, Radio: EN 300 440:2001

\*Reading range depends on reader settings.